



TOOL FEATURES

- Extra long & narrow nose design to easily get into recesses & corners without obstructed view
- One hand latch for faster reloading & reduced downtime
- Highly durable composite magazine allows for easy maintenance

FINE WIRE STAPLES

- Can be used on different surfaces and materials
- Are available in different materials
- Tip geometry suits the respective application



CONTACT & SERVICE

Our sales team
is available at:

P +43 7724 2111-671
sales@beck-fastening.com
www.beck-fastening.com

DESCRIPTION

- Rubber comfort grip ensures a non-slip handling and reduces vibrations and fatigue
- Rear exhaust with muffler for noise reduction, diverts air away from the operator and prevents the lubricant from soiling work surface
- Bottom loading magazine speeds up the reloading and keeps out the dirt
- The tool is supplied with a reversible bumper

APPLICATIONS

- Upholstering
- Case backs
- Kitchen units
- Boat interiors
- Trade shows
- Shoe making
- Picture frames
- Dust covers
- Sofas
- Insulation
- Vehicle panels

HANDLING

1. Load staples from the bottom into the magazine
2. Connect air supply
3. Avoid a dry and dirty tool by cleaning and lubricating regularly

TOOL CHARACTERISTICS

Height	Width
205 mm	42 mm
8.07 inch	1.65 inch
Length	Weight
218 mm	0.84 kg
8.58 inch	1.89 lbs

Pressure

5 - 7 bar | 70 - 100 psi

Air consumption per shot

0.50 L. | 0.018 SCF
Performance at 90 psi | 6.2 bar (0.62 MPa)

FASTENER DATA

Outside Crown	12.50 mm 0.492"
Inside Crown	11.30 mm 0.444"
Diameter	0.50 x 1.25 mm 0.019 x 0.049"
Length	6 - 16 mm ¼ - 5/8"
Magazine Capacity	110
Staple Type	ED-50 series DUO-FAST 50 BEA 95

NOISE VALUE

(EN 12549+A1 : 2008, EN ISO 4871 : 2009)

$L_{WA,1s}$: 91.19 dB (A) - $K_{WA,1s}$, 2.5

$L_{pA,1s}$: 80.70 dB (A) - $K_{pA,1s}$, 2.5

VIBRATION VALUE

(UNI ISO/TS 8662-11)

is below the declaration limit set by UNI EN ISO 12100-1/2

ACTUATION & LOADING

Actuation System: Single Shot
Dual Trigger (sequential safety kit available where a work piece safety is required)

Loading: Bottom Loading

