



**F46A
FENCE 45-315**



**TOOL-
FEATURES**

- Good balance
- High power for hardwood applications
- Rubber comfort grip ensures a non-slip handling and reduces vibration and fatigue
- Special nose for fence application
- Depth of drive adjustment

**FENCE
STAPLES**

- Patented Diamond Coating and precision divergent points for superior holding power compared to manual installation
- Hot dipped galvanized wire with minimum 350 g/m² (50 µm) zinc layer (Class 4) for maximum staple life



CONTACT & SERVICE

Our sales team
is available at:

P +43 7724 2111-671
sales@beck-fastening.com
www.beck-fastening.com

DESCRIPTION

The two divergent points and the patented Diamond Coating ensure an excellent holding power compared to manual installation.



**DIAMOND
COATING**
Highly Adhesive

**PRECISION
DIVERGENT
POINTS**



F46A FENCE 45-315

APPLICATIONS

- Fencing: batten fencing, electrified single wire, snow control fencing and light mesh fencing
- Pet enclosures, poultry fencing
- Coaxial and fiber optic utility wire applications

HANDLING

1. Load fastener from the top into the magazine
2. Connect air supply
3. Avoid a dry or dirty tool by lubricating respectively cleaning regularly

TOOL CHARACTERISTICS

| Height | Width |
|------------|-----------|
| 323 mm | 95 mm |
| 12.72 inch | 3.74 inch |
| Length | Weight |
| 367 mm | 3,35 kg |
| 14.45 inch | 7.38 lbs |

Pressure

5 - 8 bar / 70 / 120 psi

Air consumption per shot

2.56 L. / 0.090 SCF

Performances at 90psi / 6.2 bar (0.62 MPa)

FASTENER DATA

| | FENCE staples |
|---------------|----------------------------------|
| Diameter | 2,70 - 3,30 mm 0.106 - 0.130" |
| Outside Crown | 12,80 mm 0.503" |
| Inside Crown | 6,70 mm 0.264" |
| Length | 25 - 45 mm 1 - 1 3/4" |
| Capacity | 75 |
| Staple Type | F45-315 FENCE staples |

NOISE VALUE

(EN 12549+A1 : 2008, EN ISO 4871 : 2009)

$L_{WA,1s}$: 90.10 dB (A) - $K_{WA,1s}$, 2.5

$L_{pA,1s}$: 82.70 dB (A) - $K_{pA,1s}$, 2.5

VIBRATION VALUE

(UNI ISO/TS 8662-11)

is below the declaration limit set by UNI EN ISO 12100-1/2

ACTUATION & LOADING

Actuation System:
Single Shot

Loading: Top Loading

VARIATIONS

- F70G FENCE 45-315
FENCE Stapler

FASTENER PACKAGING:

Dimensions (WxHxD):
5.590x3.397x8.976"

Weight: 15.10 lbs (6,85 kg)

Quantity: 1500 pieces per pack

