



**F58AC CHN33-90B
SCR**



TOOL- FEATURES

- Good ergonomics
- Easy jam clearing system
- Switchable trigger for full sequential actuation and contact actuation

SCRAIL®

- Twice as fast as collated screws
- Eight times faster than bulk screws
- Can be used for almost all screw applications
- Easily installed, quickly removed
- Dramatically increased holding power versus nails



CONTACT & SERVICE

Our sales team
is available at:

P +1 800 239 8665
sales.us@beck-fastening.com
www.beck-fastening.com

DESCRIPTION

Are you looking for a particularly versatile tool? Then the FASCO® F58AC CHN33-90B SCR scrailer is perfect for you. It not only drives 33° Paper Tape Clipped Head Nails and 33° Paper Tape Offset Nails, but also 33° Plastic Strip SCRAIL® (fine and coarse threads). The scrailer features a copyright protected design that ensures good ergonomics and an excellent tool balance. Thanks to the new, easy jam clearing system, it's also possible to release the whole magazine.

F58AC CHN33-90B SCR

APPLICATIONS

- Decking
- Fencing
- Framing
- Manufactured housing
- Sheathing
- Millwork
- Pallets and crates

HANDLING

1. Load fastener from the top into the magazine
2. Connect air supply
3. Avoid a dry or dirty tool by lubricating respectively cleaning regularly

TOOL CHARACTERISTICS

Height	Width
368 mm	145 mm
14.49 inch	5.71 inch
Length	Weight
505 mm	3,90 kg
19.90 inch	8.59 lbs

Pressure

5 - 8 bar | 70 - 120 psi

Air consumption per shot

1.86 L. | 0.066 SCF

Performance at 90 psi | 6.2 bar
(0.62 MPa)

NOISE VALUE

(EN 12549+A1 : 2008, EN ISO 4871 : 2009)

$L_{WA,1s}$: 98.38 dB (A) - $K_{WA,1s}$, 2.5

$L_{pA,1s}$: 93.00 dB (A) - $K_{pA,1s}$, 2.5

VIBRATION VALUE

(UNI ISO/TS 8662-11)

3.98 m/s²


ACTUATION & LOADING

Actuation System: Contact
Actuation & Full Sequential
Actuation

Loading: Top Loading

VARIATIONS

F58A RHN20-90C SCR
F58AC RHN20-90C SCR



F58A CHN33-90B SCR



FASTENER DATA NAILS

Diameter	2,8 - 3,4 mm 0.110 - 0.133"
Length	50 - 90 mm 2 - 3 1/2"
Capacity	75
Nail Type	33° Paper Tape Clipped Head Nails, 33° Paper Tape Offset Nails

FASTENER DATA SCRAIL®

Diameter	2,8 - 3,5 mm 0.110 - 0.138"
Length	50 - 75 mm 2-3"
Capacity	50
SCRAIL® Type	33° Plastic Strip SCRAIL®
Drive Type	phillips® pozi (pozidriv®) torx® square versa

