



F70G RHN20-90
SCRAIL®



TOOL FEATURES

- Powerful cordless tool for 17° and 20° plastic strip SCRAIL® and nails
- Tool-free depth of drive adjustment
- Rubber comfort grip ensures a non-slip handling

SCRAIL® SUBLOC® PRO

- Aggressive double threads for squeakless subfloors
- DIAMOND COATING for maximum holding power
- Material: standard steel, SS304/A2 stainless steel
- Finish: electro-galvanized, FasCoat®

DECKING SCRAIL®

- Fine Thread SCRAIL® with a blunt “splitless” diamond point
- DIAMOND COATING for maximum holding power
- Optimized to work flawlessly in various wood species, e.g. soft wood like spruce and SYP
- Material: stainless steel A2 & A4, FasCoat®

DESCRIPTION

- Belt hook
- Full Sequential Actuation
- Works with Fasco® fuel cells
- Powerful NiMh battery
- Lights indicate battery charge

CONTACT & SERVICE

Our sales team is available at:

T +43 7724 2111-671
sales@beck-fastening.com
www.beck-fastening.com

F70G RHN20-90 SCR

APPLICATIONS

- Subflooring
- Decking
- Hiking trails
- Boardwalks
- Docks
- Siding
- Fencing
- Outdoor furniture

HANDLING

1. Load fuel cell
2. Load fastener from the rear into the magazine
3. Connect battery
4. Clean and maintain gas tool regularly

TOOL CHARACTERISTICS

Height	Width
375 mm	108 mm
14.76 inch	4.25 inch
Length	Weight
366 mm	3.53 kg
14.41 inch	7.77 lbs

Shot limit

1000 Shots / hour

Speed

2-3 Shots / second

Gas type Liquid petroleum gas

Operating temperature

-7 / 49° C | 19 / 120° F

NOISE VALUE

(EN 12549+A1 : 2008, EN ISO 4871 : 2009)

$L_{WA,1s}$: 100.20 dB (A) - $K_{WA,1s}$, 2.5

$L_{pA,1s}$: 97.20 dB (A) - $K_{pA,1s}$, 2.5

VIBRATION VALUE

(UNI ISO/TS 8662-11)

5.26 m/s²

ACTUATION & LOADING

Actuation System:

Full Sequential Actuation

Loading:

Rear Loading

BATTERY

Input Charge

220-240 VAC 50 Hz

Charge Time

1 Hour

Capacity

1650 mAh

Voltage

6 VDC

Shot / Battery

Max. 5200

Shot / Fuel Cell

Max. 1200

FASTENER DATA NAILS

Diameter	2.9 - 3.8 mm 0.114 - 0.148"
Shank	smooth ring screw barbed twisted knurled
Head	7.0 mm 0.275"
Length	50 - 90 mm 2 - 3 1/2"
Capacity	32
Nail Type	17° + 20° Plastic Strip Nails

FASTENER DATA SCRAIL®

Diameter	2.80 - 3.50 mm 0.113 - 0.138"
Head	Torx®/Star Versa Square Phillips® Pozi (Pozidrive®)
Length	50 - 75 mm 2 - 3"
Capacity	32
SCRAIL® Type	17° + 20° Plastic Strip SCRAIL®

Changes and errors excepted. All rights reserved.

FASCO®, SCRAIL®, SUBLOC® and FasCoat® are registered trademarks of the RAIMUND BECK KG.

Torx®, Phillips® and Pozi (Pozidrive®) are all trademarks of their respective owners.

VERSION
10/2020 EN