



## F70G RHN20-90 SCRAIL®



### TOOL FEATURES

- Powerful cordless tool for 17° and 20° plastic strip SCRAIL® and nails
- Tool-free depth of drive adjustment
- Rubber comfort grip ensures a non-slip handling

### SCRAIL® SUBLOC® PRO

- Aggressive double threads for squeakless subfloors
- DIAMOND COATING for maximum holding power
- Material: standard steel, SS304/A2 stainless steel
- Finish: electro-galvanized, FasCoat®

### DECKING SCRAIL®

- Fine Thread SCRAIL® with a blunt “splitless” diamond point
- DIAMOND COATING for maximum holding power
- Optimized to work flawlessly in various wood species, e.g. soft wood like spruce and SYP
- Material: stainless steel A2 & A4, FasCoat®

### DESCRIPTION

- Belt hook
- Full Sequential Actuation
- Works with Fasco® fuel cells
- Powerful NiMh battery
- Lights indicate battery charge

### CONTACT & SERVICE

Our sales team is available at:

P +39 051 6018226  
fasco@fasco-tools.com  
www.fasco-tools.com

# F70G RHN20-90 SCR

## APPLICATIONS

- Subflooring
- Decking
- Hiking trails
- Boardwalks
- Docks
- Siding
- Fencing
- Outdoor furniture

## HANDLING

1. Load fuel cell
2. Load fastener from the rear into the magazine
3. Connect battery
4. Clean and maintain gas tool regularly

## TOOL CHARACTERISTICS

Height	Width
375 mm	108 mm
14.76 inch	4.25 inch
Length	Weight
366 mm	3.53 kg
14.41 inch	7.77 lbs

### Shot limit

1000 Shots / hour

### Speed

2-3 Shots / second

**Gas type** Liquid petroleum gas

### Operating temperature

-7 / 49° C | 19 / 120° F

## NOISE VALUE

(EN 12549+A1 : 2008, EN ISO 4871 : 2009)

$L_{WA,1s}$  : 100.20 dB (A) -  $K_{WA,1s}$  , 2.5

$L_{pA,1s}$  : 97.20 dB (A) -  $K_{pA,1s}$  , 2.5

## VIBRATION VALUE

(UNI ISO/TS 8662-11)

5.26 m/s<sup>2</sup>

## ACTUATION & LOADING

Actuation System:

Full Sequential Actuation

Loading:

Rear Loading

## BATTERY

### Input Charge

220-240 VAC 50 Hz

### Charge Time

1 Hour

### Capacity

1650 mAh

### Voltage

6 VDC

### Shot / Battery

Max. 5200

### Shot / Fuel Cell

Max. 1200

## FASTENER DATA NAILS

<b>Diameter</b>	2.9 - 3.8 mm   0.114 - 0.148"
<b>Shank</b>	smooth   ring   screw   barbed   twisted   knurled
<b>Head</b>	7.0 mm   0.275"
<b>Length</b>	50 - 90 mm   2 - 3 1/2"
<b>Capacity</b>	32
<b>Nail Type</b>	17° + 20° Plastic Strip Nails

## FASTENER DATA SCRAIL®

<b>Diameter</b>	2.80 - 3.50 mm   0.113 - 0.138"
<b>Head</b>	Torx®/Star   Versa   Square   Phillips®   Pozi (Pozidrive®)
<b>Length</b>	50 - 75 mm   2 - 3"
<b>Capacity</b>	32
<b>SCRAIL® Type</b>	17° + 20° Plastic Strip SCRAIL®

Changes and errors excepted. All rights reserved.

FASCO®, SCRAIL®, SUBLOC® and FasCoat® are registered trademarks of the RAIMUND BECK KG.

Torx®, Phillips® and Pozi (Pozidrive®) are all trademarks of their respective owners.

**VERSION**  
**10/2020 EN**